

POWER MEETS RELIABILITY.


The ultimate flight experience with the best power-to-weight ratio and reliability.





582 UL 65 HP

Over 30.000 units of this easily-maintainable and robust engine have been sold.



DESCRIPTION

- 2-cylinder
- 2-stroke liquid-cooled engine with rotary valve intake
- Dual electronic ignition
- Integrated water pump and thermostat
- Exhaust system
- Carburetors
- TBO 300 hrs

WEIGHT			kg	lb
Engine			29.1	64.0
Exhaust system			5.1	11.2
2 carburetors			1.8	4.0
Electric starter			3.5	7.7
PSRG** "E" / i = 2.62 / 3.0 / 3.47 / 4.0			11.2	24.7
PERFORMANCE				
48.0 kW 65		65 hp	6500 1/min.	
TORQUE				
75 Nm		55.3 ft. lb.	3 ft. lb. 6000 1/min.	
MAX RPM*				
			68	300 1/min.
BORE		ST	ROKE	
76.0 mm	2.99 in	64.	0 mm	2.52 in
DISPLACEMENT FUEL				
580 cm³	35.4 cu in	r	min. MON 8 m	5 RON 91* in. AKI 87*

^{*} leaded, unleaded, AVGAS 100LL, Ethanol 10

UL: ASTM compliant





^{**} Propeller speed reduction gearbox